

Performance Data

Warranty (Years)	VLT (%)	UV Rejection (%)	Solvent Resistance	Stone Chip Resistance (SAE-J400)	Aging Test	Peel Strength (72h)	Peel Strength (20 min)	Gloss (60°)	Elongation at Break (ASTM D882)	Tensile Strength (MPa) (ASTM D882)	Liner (µm)	Adhesive (µm)	Top Coat (µm)	TPU (µm)	Thickness (µm)
5			NDE	Pass	NDE	>400 n/m	>400 n/m	>90	≥250	20	92	60	9	125	194
5			NDE	Pass	NDE	>400 n/m	>400 n/m	25	≥250	20	92	60	7	125	192
7			NDE	Pass	NDE	>400 n/m	>400 n/m	>85	>300	20	92	45	9	150	214
5			NDE	Pass	NDE	>400 n/m	>400 n/m	20	≥250	15	75	30	7	125	177
5	70	≥99	NDE	Pass	NDE	>400 n/m	>400 n/m	>90	>300	15	75	27	9	130	166
5	25	≥95	NDE	Pass	NDE	>400 n/m	>400 n/m	>90	≥250	16	100	26-30	8-12	150	200
5	35	≥95	NDE	Pass	NDE	>400 n/m	>400 n/m	>90	≥250	16	100	26-30	8-12	150	200
5	50	≥95	NDE	Pass	NDE	>400 n/m	>400 n/m	>90	≥250	16	100	26-30	8-12	150	200